

What is Peacock Wax?

A natural, innovative and luxurious wax finish in a 60ml tin!

Handmade in our own workshop, Peacock Wax is a unique blend of the world's finest traditional oils and waxes. This lustrous finish provides a protective film for both previously sealed wood and bare metal surfaces.

Although initially developed for both our saws and the professional cabinetmaker as a one-stop wax to both finish and protect commissions and furthermore maintain tools whilst in use, we recognise that Peacock Wax would be suitable and beneficial to be used in a host of other industries.

Wood Protection:

Suitable for use on previously sealed wood, Peacock Wax will protect and enhance a variety of finishes including:

- Skelton Saws Peacock Oil
- French Polish (Shellac)
- Oil finishes
- Modern oil / wax blends e.g. Danish Oils

Metal Protection:

Suitable for use on both ferrous and non-ferrous steels, Peacock Wax provides a protective layer that seals against oxidation therefore maintaining the brightness of both brass and bronze.

For ferrous metals the wax can either be used on bare metal for example on tools / cast iron or previously blued surfaces.

The Benefits

- Easy and quick to use
- Hard-wearing
- It is a superior yet as natural as possible finish. As a family of allergy sufferers, it is always important for us to create something that will be suitable for the sensitive user. Peacock Wax is a blend of natural ingredients and is free from any harsh, overpowering odours, emitting only a slight but pleasant citrus smell
- Enhances the finish beneath, providing an almost glow to the piece
- Ideal for using on the sides of saw plates and the soles of plane irons, making the tool frictionless
- Provides an element of weather-proof protection
- It doesn't finger mark
- Has a tactile silky feel to the touch once hardened
- Free from any artificial drying agents
- Contains only the finest proven raw ingredients, some dating back to biblical times
- It's non-sticky. Unlike most other waxes available, Peacock Wax doesn't soften through the warmth of your hands thus making it non-transferrable

How to Use

Always wear suitable gloves when applying.

On opening your tin of Peacock Wax, you will notice that the wax appears hard mimicking almost a bar of soap, do not be alarmed – it is magic!

- Using a lint free cloth gently circulate it over the top of the wax. This friction will allow the wax to flow
- Apply the wax directly to the surface of your given piece covering as much as possible from the cloth. You will notice that a little goes a long way, and are aiming for a very thin layer on your piece
- Allow to dry for 10-15 minutes or until touch dry. You will notice that when dry the wax will take on a dull almost smoky appearance
- Using a new clean lint free cloth buff until a deep sheen is achieved. At this point a further application can be applied if required. (This finish will allow for build up using subsequent coats)
- Best results can be seen 24-48 hours after application and unlike most wax finishes Peacock Wax will continue to harden over time

SAFETY DATA SHEET

(REACH regulation (EC) - n°1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name; Skelton Saws Peacock Wax

Product code; PW01 60ml

Product colour; Natural

1.2. Relevant identified uses of the substance or mixture and uses advised against

Wood / Metal Finishing Wax

1.3. Details of the supplier of the safety data sheet

Registered company name: Skelton Saws

Address: 8 The Pheasantry, Crossgates, Scarborough, North Yorkshire, YO12 4UH

Telephone: 01723 448202.

skeltonsaws@gmail.com

www.skeltonsaws.co.uk

1.4. Emergency telephone number:

. Association/Organisation:

Other emergency numbers

UK - National Poisons Information Service Phone: 191 22 5131

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Flammable (R 10).

Harmful; may cause lung damage if swallowed (R 65).

Repeated exposure may cause skin dryness or cracking (R 66).

Splashes in the eyes may cause eye irritation. (H319).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard Symbols:



Risk Phrase:

R 10 Flammable.

R 65 Harmful; may cause lung damage if swallowed.

R 66 Repeated exposure may cause skin dryness or cracking.

H319 Splashes in the eyes may cause eye irritation.

Safety phrase:

S2 Keep out of the reach of children.

Skelton Saws Peacock Wax Date of issue :01/12/2020

S46 If swallowed, seek medical advice immediately and show this container or label.

S29 Do not empty into drains.

2.3. Other hazards: No data available.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

No substances fulfil the criteria set forth in annexe II section A of the REACH regulation (EC) n° 1907/2006. **3.2. Mixtures Composition:**

Identification	(EC) 1272/2008 (CLP)	67/548/EEC	%
ALIPHATIC HYDROCARBON CAS: 64742-47-8 EC: 265-149-8	Asp. Tox. 1, H304 EUH066	Xn; R65 Xn; R66	< 50
ORANGE TERPENES CAS: 8028-48-6 EC: 232-433-8	Flam. Liq.3, H226 H304	Xn; R65 Xn; R10 R38	< 25

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation;

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the

label. **4.2. Most important symptoms and effects, both acute and delayed** No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use:

Skelton Saws Peacock Wax Date of issue :01/12/2020

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

For non fire-fighters

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapours.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For fire-fighters

Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapours. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Skelton Saws Peacock Wax Date of issue :01/12/2020

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

No data available.

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- **Eye / face protection** Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- **Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR)) - PVA (Polyvinyl alcohol)

Recommended properties:

- Impervious gloves in accordance with standard EN374

- **Body protection** Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- **Respiratory protection** Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387: - A1 (Brown).

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state :	Malleable Solid
------------------	-----------------

Important health, safety and environmental information

Skelton Saws Peacock Wax Date of issue :01/12/2020

pH :	Not relevant
Boiling point/boiling range :	Not relevant
Flash point interval :	>67°C (153°F)
Vapour pressure :	Not relevant
Density :	Not relevant
Water solubility :	Insoluble
Melting point/melting range :	Not relevant
Self-ignition temperature :	180°C (356°F)
Decomposition point/decomposition range :	Not relevant

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effect

Skelton Saws Peacock Wax Date of issue :01/12/2020

General Information;

This product has low toxicity. Only large volumes may have adverse impact on human health.

Hazard of Substance;

Aspiration Hazard.

Route of entry;

Skin and / or eye contact.

Ingestion;

Pneumonia may be the result if vomited material containing solvent reaches the lung.

Inhalation;

Not relevant at normal room temperatures. When heated, irritating vapours may be formed.

Eye contact;

Splashes may irritate.

Skin contact;

Acts as a defatting agent on skin. May cause cracking of skin and eczema.

Other health effects;

This substance has no evidence of carcinogenic properties.

Medical considerations;

Avoid vomiting and normal rinse of the stomach because of risk of aspiration.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION**12.1. Toxicity****12.1.1. Substances**

No aquatic toxicity data available for the substances.

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

CAUTION: Oil cloths can self-combust. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Skelton Saws Peacock Wax Date of issue :01/12/2020

SECTION 14 : TRANSPORT INFORMATION

This product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID). Tariff code 2901 1000.

No transport warning signs are required.

Maximum of 6L per unit.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Particular provisions:**

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Title for H, EUH and R indications mentioned in section 3:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Splashes in the eyes may cause eye irritation.
R 10	Flammable.
R 65	Harmful: may cause lung damage if swallowed.
R 66	Repeated exposure may cause skin dryness or cracking.